


### Product Group MFK

Machine feet made of stainless steel with rubber base (to cope slopes on the floor and equipment)




#### Standard Colours

- white

#### Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The rounded design of this type makes cleaning easy.
- The rubber pressed into the foot plate meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 20°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

| D   | F max. | H  | M   | WAF | 50 | 70 | 100 | 150 | 180 | 230 | 310 |
|-----|--------|----|-----|-----|----|----|-----|-----|-----|-----|-----|
| mm  | kg     | mm |     | mm  | mm | mm | mm  | mm  | mm  | mm  | mm  |
| 75  | 800    | 21 | M12 | 10  | x  | x  | x   | x   | x   |     |     |
| 75  | 800    | 21 | M16 | 13  |    | x  | x   | x   | x   | x   | x   |
| 75  | 800    | 21 | M20 | 15  |    | x  | x   | x   | x   | x   | x   |
| 75  | 800    | 21 | M24 | 19  |    | x  | x   | x   | x   | x   | x   |
| 75  | 800    | 21 | M30 | 24  |    |    |     |     | x   | x   |     |
| 100 | 2000   | 36 | M12 | 10  | x  | x  | x   | x   | x   |     |     |
| 100 | 2000   | 36 | M16 | 13  |    | x  | x   | x   | x   | x   | x   |
| 100 | 2000   | 36 | M20 | 15  |    | x  | x   | x   | x   | x   | x   |
| 100 | 2000   | 36 | M24 | 19  |    | x  | x   | x   | x   | x   | x   |
| 100 | 2000   | 36 | M30 | 24  |    | x  | x   | x   | x   | x   | x   |
| 125 | 3000   | 40 | M12 | 10  | x  | x  | x   | x   | x   |     |     |
| 125 | 3000   | 40 | M16 | 13  |    | x  | x   | x   | x   | x   | x   |
| 125 | 3000   | 40 | M20 | 15  |    | x  | x   | x   | x   | x   | x   |
| 125 | 3000   | 40 | M24 | 19  |    | x  | x   | x   | x   | x   | x   |
| 125 | 3000   | 40 | M30 | 24  |    | x  | x   | x   | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ----> MFK 100 M16 x 100