


Product Group KD

Grommets




Standard Colours

- black RAL 9005

Material

- Plasticised PVC (PVC-P), app. 60 Shore A



Product information

- Burning behaviour: The Daimler-Benz delivery specification 5307 Cat. 2 is fulfilled
- Harmless, phthalate-free plasticiser (toys, food contact)
- Colours and stabilizers are food safe.
- *) = Grommet KD 706 is one-side thin-walled closed

Product options on inquiry

- Special colours (colours, minimum quantities, set-up costs, pricing and surcharges)
- Production in different, medium Shore A hardnesses in TPE-V from 70 Shore A possible (short-term temperature up to 140 °C, continuous service temperature 120 °C).
- Special designs in all elastomers (rubber, silicone, etc.) are not possible.
- PVC-P (soft) electrical diverting

Order Number	d	D	D1	H	H1
	mm	mm	mm	mm	mm
KD 701	4,5	9,5	6,5	6	1,2
KD 715	5	11	8	6	1,5
KD 702	6	11,5	8	6	1
KD 717	6	11,5	9	6	1,5
KD 707	6	12,7	9,8	8	2
KD 710	8	18	14	6	1
KD 209	8	14	10	5,5	1,5
KD 716	8	14	10	8	1,5
KD 703	9	16	11	6,5	1
KD 712	9	16	12	6,5	1,5
KD 1	10	18	13	5,5	1
KD 711	10	18	12	8	1,2
KD 12	10	18	13	6	1,5
KD 709	10	17,5	12	7	2
KD 11	10	18	13	8	3
KD 704	10	18	12	11	4
KD 10	12	20	15	7	1,5
KD 9	12	20	15	7	2



Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

Order Number	d	D	D1	H	H1
	mm	mm	mm	mm	mm
KD 2	12	22	17	10	4
KD 3	13	21	16	7	1,5
KD 215	15	25	18	9	2
KD 6	16	25	20	7	1,5
KD 7	16	25	20	7	2
KD 8	16	25	20	8	2,5
KD 216	16	30	24	11	3
KD 706 *	20	33	30	11	3
KD 223	23	39	29	10	1,5
KD 5	23	33	28	8	2
KD 323	23	39	29	10	3
KD 4	25	35	30	9	3
KD 332	32	46	38	11	3