



### Product Group MFSL

Machine feet made of zinc-plated steel, optional with antislip-pad (A)



#### Material

- Base body: zinc-plated steel
- Antislip pad: NBR 70 Shore



#### Product information

- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Especially for large machine construction

#### Product options on inquiry

- Delivery with additional steel nut possible.

| D   | F max. | H  | H1 | M   | WAF | 100 | 150 | 200 | 225 |
|-----|--------|----|----|-----|-----|-----|-----|-----|-----|
| mm  | kg     | mm | mm |     | mm  | mm  | mm  | mm  | mm  |
| 80  | 3000   | 19 | 33 | M16 | 24  | x   | x   | x   |     |
| 80  | 3500   | 19 | 33 | M20 | 24  | x   | x   | x   | x   |
| 80  | 4000   | 19 | 33 | M24 | 24  | x   | x   | x   | x   |
| 100 | 4000   | 20 | 34 | M20 | 24  | x   | x   | x   | x   |
| 100 | 4500   | 20 | 34 | M24 | 24  | x   | x   | x   | x   |
| 100 | 5000   | 20 | 36 | M30 | 30  | x   | x   | x   | x   |
| 120 | 4500   | 22 | 36 | M20 | 24  | x   | x   | x   | x   |
| 120 | 5000   | 22 | 36 | M24 | 24  | x   | x   | x   | x   |
| 120 | 6000   | 22 | 38 | M30 | 30  | x   | x   | x   | x   |
| 159 | 5000   | 23 | 36 | M20 | 24  | x   | x   | x   | x   |
| 159 | 6000   | 23 | 36 | M24 | 24  | x   | x   | x   | x   |
| 159 | 7000   | 23 | 38 | M30 | 30  | x   | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ----> MFSL 80 M10x 100 (A)